

TAITA CHEMICAL CO LTD (TTC) 12TH FL, B AREA, CHINA GENERAL PLASTICS BLDG, NEI HU DISTRICT 39 JI HU RD, TAIPEI 114 TW



1000(x)

Acrylonitrile Butadiene Styrene (ABS), pellets

(x) - May have optional suffix A-Z indicating different color.

Flammability	Value	Test Method
Flame Rating		
1.5 mm, ALL	НВ	UL 94
3.0 mm, ALL	НВ	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.5 mm	PLC 3	
3.0 mm	PLC 3	
High Amp Arc Ignition (HAI)		UL 746
1.5 mm	PLC 0	
3.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 1	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 0	UL 746
Arc Resistance	PLC 7	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	60.0°C	
3.0 mm	60.0°C	
RTI Imp		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0°C	
RTI Str		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	

Page 1 of 1 Form Number: E50263-241880

Report Date: 1983-10-13 Last Revised: 2013-05-10

UL and the UL logo are trademarks of UL LLC Copyright © 2019 All Rights Reserved. | www.ul.com