Taita Chemical Company, Limited



Head Office: 12FL, No.39, Ji-Hu, Taipei, Taiwan

Tel: (886) 2-8751-6888 Fax: (886) 2-2650-3260 **Product Information**

Ver. : 1.0

台達通用及耐衝擊聚苯乙烯

TAITAREX GPPS/HIPS

(General Purpose Polystyrene) GPPS 861F

Characteristics

Applications

- Injection Grade
- The most state of the art from US NOVA CHEMICAL
- Low Residual Monomer
- Mold Dimension Stability
- Good Transparency
- Easy Processing

- house hard wares
- TPR compounding
- cassette, toys.

Physical Properties

Properties	ASTM method	Test Condition	Unit	Typical Value
Specific Gravity	D542			1.05
Melt Flow Index	D1238	200°ℂ,5 kg load	g/10min	12.0
Tensile Strength at Yield	D638	23℃,1/8" Sample	kg/cm2	440
Elongation at Break	D638	23℃,1/8" Sample	%	2.0
Izod Impact Strength	D256	23°C ,A method,notched 1/4"×1/2"×5/2"	kg-cm/cm	1.3
Vicat Softening Temperature	D1525	1 kg load,3 mm Thick (120 $^{\circ}\mathrm{C}$ /hr)	°C	97
Flammability	UL-94	1/16" Sample	File No. E50263	94HB
Residual SM monomer	Internal	GC	ppm	< 300
Haze		2.8mm thick	%	0.4

Note: The data listed represent average values and are believed to be reliable. They are given for information; no guarantee of their accuracy is made.