## TAITA CHEMICAL CO LTD (TTC)

12TH FL, B AREA, CHINA GENERAL PLASTICS BLDG, NEI HU DISTRICT 39 JI HU RD, TAIPEI 114 TW



## 1200+

Acrylonitrile/Styrene (A/S), pellets, copolymer

+ - With suffix "L" or "LL".

Flammability	Value	Test Method
Flame Rating		
1.5 mm, NC, BL	HB	UL 94
3.0 mm, NC, BL	HB	UL 94
3.0 mm, NC, BL	HB40	IEC 60695-11-10, -20
1.5 mm, NC, BL	HB75	IEC 60695-11-10, -20
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.5 mm	PLC 4	
3.0 mm	PLC 3	
High Amp Arc Ignition (HAI)		UL 746
1.5 mm	PLC 0	
3.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 2	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 0	UL 746
Arc Resistance	PLC 7	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Str		UL 746
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	

UL and the UL logo are trademarks of UL LLC Copyright © 2019 All Rights Reserved. | www.ul.com

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 smallscale test data is intended solely for determining the flammability of plastic materials used in the components and parts of endproduct devices and appliances, where the acceptability of the combination is determined by UL. Form Number: E50263-241904 Report Date: 1988-09-21 Last Revised: 10/24/2003